

GOLD FLUSH-FIT

IP40 FLUSH-FIT DISTRIBUTION BOXES HOLLOW WALLS

Description: IP40 FLUSH-FIT BOX 1x12 MOD. PE+N

Reference:

GPE12PO/PH/RR

Characteristics:

Product type:	IP40 Flush-fit hollow walls distribution box 12 modules, white door and screwed neutral and earth bar
Exterior dimensions (Height x Width x Depth):	284x316x97 mm
Dimensions of the flush-fit gap (HxWxD):	256x288x72 mm
Number of modules:	1x12 DIN rail
Installation:	Flush-fitted hollow walls
Color:	RAL 9003
Window:	Opaque
Weight (kg):	1,36
Cable entry:	Bottom: 1xM50/M40 4xM25/M20 5xM25/M16 - Rear: 2xM40/M32 4xM25 - Left: 2xØ32 - Right: 2xØ32
Components:	Cable section: 6x(2,5-6 mm ²)+6x(4-10 mm ²)+1x(10-25 mm ²)+1x(16-35 mm ²)
Materials:	Halogen-free plastic materials. Base: V0 PS. Frame: ABS
Lid-window-door material:	ABS

Technical data:

Degree of protection:	IP40
Resistance to impact:	IK08
Glow wire resistance:	850 °C
Ball pressure test:	70 °C
Ambient temperature range:	-25 °C / +40 °C
Maximum operating voltage:	1000 V AC / 1500 V DC
Rated current:	125A
Double insulation:	Class II

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 62208, IEC 61439-1
Certificates:	



Codes:

EAN:	8431044188270
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000214

GOLD FLUSH-FIT

IP40 FLUSH-FIT DISTRIBUTION BOXES HOLLOW WALLS


Description: IP40 FLUSH-FIT BOX 1x12 MOD. PE+N

Reference: GPE12PO/PH/RR



Detailed drawing:

 <http://www.ide.es/downloads/planos/pdf/GPE12POPHRR.pdf>

 <http://www.ide.es/downloads/planos/dxf/GPE12POPHRR.dxf>

 <http://www.ide.es/downloads/planos/stp/GPE12POPHRR.stp>

Exterior dimensions (Height x Width x Depth):

284x316x97 mm

Dimensions of the flush-fit gap (Height x Width x Depth):

256x288x72 mm

Sustainability:

RoHS - REACH

Supply:

Supplied in individual cardboard packaging. When several items are sent together, they are bundled together with transparent film.

Packaging units: 8

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Tertiary and residential sectors. For use indoors, specially designed for installation in pre-fabricated or plasterboard walls, flats, houses, offices, hotels, etc.