

GLASS SERIES

IP55 POLYESTER WALL-MOUNTING CABINETS

Description: IP55 POLYESTER WALL-MOUNTING CABINET 500x500x300 OPAQUE DOOR W/HANDLE

Reference:
POL505030

Characteristics:

Product type:	Polyester wall-mounting cabinet
Dimensions cabinet:	(AxBxC) 510x500x312 mm
Installation:	Surface
Type of door:	Single opaque door
Locking:	3-mm 3-point sealable double bit insert lock with retractable handle
Finish:	Double insulation: Class II
Colour:	RAL 7035
Mounting plate:	Without mounting plate
Weight (kg):	9,8
Materials:	Fibreglass-reinforced polyester
Thickness:	Side panel 4 mm. Top and bottom 3 mm. Door and rear 3,5 mm.
Sealing gasket:	Injected polyurethane sealing gasket
Door material:	Fibreglass-reinforced polyester
Capacity:	
Max. cabinet load:	
Max. mounting plate load:	40 kg
Max. door load:	8 kg

Technical data:

Degree of protection:	IP55
NEMA degree of protection:	
Resistance to impact:	IK10
Ambient temperature range:	-30 °C / +60 °C
Maximum operating voltage:	1000 V AC / 1500 V DC

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 62208, IEC 61439-1
Certificates:	



Codes:


EAN:	8431044157689
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000261

GLASS SERIES

IP55 POLYESTER WALL-MOUNTING CABINETS



Description: IP55 POLYESTER WALL-MOUNTING CABINET 500x500x300 OPAQUE DOOR W/HANDLE

Reference: POL505030



Standard drawing



Detailed drawing:  <http://www.ide.es/downloads/planos/pdf/POL505030.pdf>
 <http://www.ide.es/downloads/planos/dxf/POL505030.dxf>
 <http://www.ide.es/downloads/planos/stp/POL505030.stp>

Cable entry: -
Wall fixing: (HeightxWidth) 368x552 mm
Inside usable space: (HeightxWidthxDepth) 412x405x274 mm
No. Hinges: 2

Body to be flush-fitted: -
Wall fixing material: -
Glass door with transparent panel: -
Door profiles: -

Sustainability:

RoHS - REACH

Supply:

Supplied individually shrink-wrapped and protected with cardboard at top and bottom. The accessories for fitting the mounting plate are fitted on the cabinet. Plate supplied in individual packaging if requested as an accessory.

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Industrial environments and outdoor facilities. food, chemical and pharmaceutical industries, transformer sub-stations and outdoor areas where durability and resistance against chemicals and UV rays are necessary.