

# ETF2000

Hygrostat

nVent

HOFFMAN

CONNECT AND PROTECT



This relative humidity hygrostat is available as pre-set, ETF200, or adjustable, ETF2000. It activates a device, such as a heater, within the enclosure, either at the pre-set level, 65%, when the relative humidity has been exceeded, or at a level set by the user, which could be between 40-90% humidity.

CE UK EAC

<b>Description</b>	Adjustable hygrostat
<b>Setting range</b>	40% to 90%
<b>Weight (kg)</b>	0.05
<b>Item no.</b>	ETF2000

**Description:** Mechanical hygrostat designed to control heaters when the pre-set or fixed relative humidity is exceeded. The relative humidity must be kept above the dew point to prevent condensation and corrosion inside the enclosure. Mounting clip for 35 mm DIN rail (EN 60715).

**Material:** Plastic according to UL94 V-0

**Switch capacity:** 250 V AC, 5 A. DC, 20 W, (30 W ETF2000).

**Operating temperature:** 0 °C to +60 °C.

**Service life:** > 50,000 cycles.

**Connection:** 2 pole terminal for 2.5 mm<sup>2</sup>.

**Protection:** IP 20.

**Approvals:** CE, EAC, cULus\_UL Listed.

**Finish:** RAL 7035.

**Pack quantity:** 1 piece.