

Sedi operative:

Via Liguria, 52 - 37060 Lugagnano di Sona (VR)
Tel. +39 045 6230 855 / 045 989477
info@italweberelettra.it - www.italweberelettra.it

Via Per Inveruno, 103 - 20020 Busto Garolfo (MI)
Tel. +39 0331 537508 - Fax +39 0331 537504
info@italweberelettra.it - www.italweberelettra.it

TYPE TESTED ISOLATING THOROIDAL TRANSFORMER

CODE	OTR0250AA07
-------------	--------------------

NORM	EN 61558-1 EN 61558-2-4 UL 5085 CSA C22.2 N°66
-------------	---

CLIENT	
---------------	--

TRANSFORMERS GENERAL FEATURES

TYPE	: associated, not short-circuit resistant by construction
MOBILITY	: fixed
COOLING	: air/natural
STANDARDS	: EN 61558-1 , EN 61558-2-4 , UL 5085 , CSA C22.2 N°66
PROTECTION CLASS	: I
INSULATION CLASS	: F
TEMPERATURE CLASS	: B
MAX AMBIENT TEMPERATURE	: +40 °C
PHASES	: 1
INDEX PROTECTION TRANSFORMER	: IP 00
TIME OF OPERATION	: continuous
FREQUENCY	: 50/60 Hz
WINDINGS WITH	: Copper wire
ELECTROSTATIC SHIELD	: No
DIELECTRIC STRENGTH	: 4 KV
CONTAINMET BOX	: No
TERMINALS DISPOSITION	: 1 Side
TYPE OF TERMINALS	: Free wires L=15cm
FIXING KIT	: Yes, n°1 , composed of one metal disk and two black rubber discs

ELECTRICAL FEATURES

WINDING	TENSION	POWER
	V	VA
PRIMARY	230	250
SECONDARY	230	250

Sedi operative:

Via Liguria, 52 - 37060 Lugagnano di Sona (VR)
Tel. +39 045 6230 855 / 045 989477
info@italweberelettra.it - www.italweberelettra.it

Via Per Inveruno, 103 - 20020 Busto Garolfo (MI)
Tel. +39 0331 537508 - Fax +39 0331 537504
info@italweberelettra.it - www.italweberelettra.it

DIMENSIONAL FEATURES

DIAMETER mm	HEIGHT mm	WEIGHT kg
115	60	2,3

DIMENSIONS INDICATED ABOVE ARE INDICATIVE FOR TRANSFORMER

**TRANSFORMERS OTR SERIE ARE TESTED BY CSA WITH cCSAus MARK (FILE N° 203609)
AND BY DEKRA WIRH ENE05/KEMA KEUR MARK**

**PLEASE VERIFY ALL FEATURES INDICATED IN THIS DATA SHEET AND COMMUNICATE
ANY CHANGES, IF REQUIRED, BEFORE ORDER**