

# TLC87035

Compact design light

nVent

HOFFMAN

CONNECT AND PROTECT



This energy efficient fluorescent enclosure light can be mounted in many different ways, as well as directly on 19" profiles, in any enclosure, and helps when maintenance is performed in the field.

CE EAC

IP 20

Finish	Light grey (RAL 7035)
Operating voltage	230 V, 50/60 Hz
Item no.	TLC87035

**Description:** Lighting system with a compact design, suitable for all types of enclosures or racks. It has three possible fixing possibilities: magnetically, screw mounting with a variable distance between holes and/or snap-into 19" rack. It is an electronically operated device and has a service life of 10,000 h. The body of the lighting system is made of PC-ABS. An integrated connector allows the activation of the lamp by a door switch by using the TLCS product without performing any additional wiring. It is provided with a protection cap made of PC and the colour of the light is cold white.

**Lamp type:** Fluorescent lamp T5/G5.

**Luminosity:** 480 Lm.

**Power consumption:** 8 W.

**Operating temperature:** -15 °C to +45 °C.

**Dimensions:** 448 x 54.5 x 26 mm.

**Connections:** 2x0.75 mm<sup>2</sup> open end cable (1.5 m long), 2x0.75 mm<sup>2</sup> female mini-connector for door switch use.

**Approvals:** CE, EAC.

**Delivery:** 1 light with fix mounted connection cable, integrated magnets and mounting screws.