

universal busbar support (01230)



The picture may show a similar product.

Description

Part No.: **01230**000

universal busbar support

for busbars 30 - 120 x 10, double-T and triple-T section

Product group 06

Subgroup 24

pack size 4

EAN 4021267012304

catalog page 2015 : 4.12

ECLASS 6.1 27400607

ECLASS 7.1 27400607

ETIM 4.0 EC001166

ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2020

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2020

Electrical data IEC

rated voltage (IEC) AC: 690 V

rated isolation voltage U_i AC: 1000 V

rated surge voltage U_{imp} : 8 kV

The insulation performance of the article depends on the installation conditions.

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.0 W.

(The power dissipation at full load would be 0.0 W.)

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) DC: 1500 V

Short-circuit withstand capacity: Surge current strength > 100kA at Busbar support separation 400 mm

Mechanical data

W x H x D: 30 x 580 x 65

weight: 50.0 kg/100

poles: 3-pole

for busbars: 30 - 120 x 10, double-T and triple-T section

Reference

Torque for the screws of the busbar support $M_d = 4\text{Nm}$

<https://pim.woehner.de/EN/EN/1000043994>