

## universal busbar support (01485)



The picture may show a similar product.

### Description

Part No.: **01485000**

universal busbar support

4-pole with internal screw holes

for busbars 12, 15, 20, 25, 30 x 5, 10

### System

60Classic

### Advantages of the product

With internal screw holes

can also be used as centre support

With the 4th pole, the width of the busbar can be set independent of L1, L2 and L3.

**Product group** 06

**Subgroup** 12

**pack size** 10

**EAN** 4021267014858

ECLASS 6.1 27400607  
ECLASS 7.1 27400607  
ETIM 4.0 EC001166  
ETIM 5.0 EC001166

## Approvals

### Standards

IEC 61439-1:2020  
UL 508

### Approvals

CSA, UL, DNV GL



type number: 485

UL file: E123577, UL category (for USA): NMTR2 <https://www.ul.com>  
UL file: E123577, UL category (for Canada): NMTR8 <https://www.ul.com>  
CSA file: 110285, CSA class: 3211-37 <https://directories.csa-international.org>  
CCC approval: no certification required

## Technical data

### Details IEC

#### Standards

IEC 61439-1:2020

#### Electrical data IEC

rated voltage (IEC) AC: 800 V

rated frequency (IEC): 50 / 60 Hz

rated isolation voltage  $U_i$  AC: 1000 V

rated surge voltage  $U_{imp}$ : 8 kV

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.0 W.

(The power dissipation at full load would be 0.0 W.)

Kurzschlussfestigkeit:

Siehe Kurzschlussdiagramm im Bereich Download

## Details UL

### Standards

UL 508

### Electrical data UL

rated voltage (UL) AC: 600 V

rated frequency (UL): 50 / 60 Hz

### Mechanical data

W x H x D: 20 x 245 x 51

weight: 26.6 kg/100

poles: 3-pole+N

for busbars: 12, 15, 20, 25, 30 x 5, 10

<https://pim.woehner.de/EN/EN/1000043931>