wöhner

spare part busbar adapter 250 A (32595)

The picture may show a similar product.

Description

Part No.: 32595000
CrossLink® 60Classic
spare part busbar adapter 250 A
busbar adapter base
with CrossLink® interface

System
60Classic

Product group	05
Subgroup	58

pack size	2
EAN	4021267325954

ECLASS 6.1	27370304
ECLASS 7.1	27370304
ETIM 4.0	EC001531
ETIM 5.0	EC001531

Approvals

Standards
IEC 61439-1:2020

CCC approval: no certification required

Technical data

Details IEC
Standards
IEC 61439-1:2020

Electrical data IEC
Rated current (IEC): 250 A
rated voltage (IEC) AC: 690 V

rated voltage (IEC) DC: 440 V

rated isolation voltage U_i AC: 800 V
rated surge voltage U_{imp} : 6 kV

power dissipation of the article:
The power dissipation at a typical load of 80 % results to 15.9 W.
(The power dissipation at full load would be 24.8 W.)

Supplementary data IEC
The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) AC: 725 V
max. permitted voltage (IEC) DC: 462 V

Mechanical data

W x H x D:	184 x 210 x 17
weight:	75.5 kg/100
poles:	3-pole

Application notes

There must be a clearance of at least 10 mm above the article to remove it from the busbar system.

https://pim.woehner.de/EN/EN/1000047272