

# ABS BASIC SERIES

## ABS WALL-MOUNTING CABINETS

Description: ABS WALL-MOUNTING CABINET 700x500x250 OPAQUE DOOR

Reference:

**ABS705025**

### Characteristics:

Product type:	Wall-mounting cabinet
Dimensions cabinet:	(AxBxC) 700x500x250 mm
Installation:	Surface
Type of door:	Opaque door
Locking:	Triangle lock
Finish:	Double insulation: Class II
Colour:	RAL 7035
Mounting plate:	Mounting plate: 1-mm galvanized steel
Weight (kg):	10,1
Materials:	HB ABS
Thickness:	
Sealing gasket:	
Door material:	
Capacity:	
Max. cabinet load:	
Max. mounting plate load:	
Max. door load:	

### Technical data:

Degree of protection:	IP54
NEMA degree of protection:	
Resistance to impact:	IK08
Ambient temperature range:	-25 °C / +40 °C
Maximum operating voltage:	1000 V AC / 1500 V DC

### Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 62208
Certificates:	



### Codes:

EAN:	8431044370255
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000261

# ABS BASIC SERIES


## ABS WALL-MOUNTING CABINETS

Description: ABS WALL-MOUNTING CABINET 700x500x250 OPAQUE DOOR

Reference: ABS705025



Standard drawing

**Detailed drawing:**  <http://www.ide.es/downloads/planos/pdf/ABS705025.pdf>  
 <http://www.ide.es/downloads/planos/dxf/ABS705025.dxf>  
 <http://www.ide.es/downloads/planos/stp/ABS705025.stp>

**Cable entry:**

**Wall fixing:** (FxG) 580x425 mm

**Inside usable space:** (DxE) 657x450 mm

**No. Hinges:**

**Body to be flush-fitted:** -

**Wall fixing material:**

**Glass door with transparent panel:**

**Door profiles:**

### Sustainability:

RoHS

### Supply:

Supplied in individual cardboard packaging.

### Product end of life:

It does not require specific recycling operations.

### Recommended applications:

Specially designed for applications in the industrial automation and control sector.